



PATIO &
PAVING
FOND DU LAC
STEPPERS

GEOLOGY

dolomitic limestone

BASIC USE

on patios and walkways; stone is dryset
in gravel bed or mortared in

COLOR RANGE

gray, light gray, buff, and white

CONSISTENCY PER PALLET

somewhat consistent

**WEIGHT CALCULATED IN
INCHES**

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

PALLET

4,000 pounds

COVERAGES

1" to 2" 80 square feet / ton
1-3/4" to 2-1/2" 65 ft²/ton

DIMENSIONS

l: 8" to 24"

h: 1" to 2" or

h: 1-3/4" to 2-1/2"

w: 8" to 24"

note: lengths and widths are irregular
shapes 8 inches to 24 inches in diameter

TYPICAL PIECE

ends irregular; natural cleft top and
bottom; natural split sides; stone is
random shapes

PART NUMBERS

1" to 2": 1PATBUE02015TN

1-3/4" to 2-1/2": 1PATBUE02017TN

ASTM TESTING DATA

FOND DU LAC C97

water absorption—0.36%

density—174.2 pcf

FOND DU LAC C99

modulus of rupture—1,470 psi

FOND DU LAC C170

compressive strength

w/rift—29,040 psi

compressive strength

across rift—34,240 psi

FOND DU LAC C880

flexural strength—1,740 psi

