

CASTLE
ROCK
OILED NUBUCK
CASTLE ROCK



GEOLOGY

limestone - quarried in USA

COLOR RANGE

buff, brown, tans, gray and black

CONSISTENCY PER PALLET

somewhat consistent

PALLET AMOUNTS

FULL VENEER (sold/ton) 4,000lbs each

THIN VENEER (sold/each) QB or BX

QUANTITY BOX - QB

1 - 100 sq ft of flats

1 - 50 lin ft of corners

SMALL BOX - BX

24 - 8 sq ft flat boxes, 192 total ft

20 - 8 lin ft corner boxes, 160 total feet

ASTM TESTING DATA

OILED NUBUCK C97

water absorption—7.27%

OILED NUBUCK C97

density—134.1 pcf

OILED NUBUCK C97

specific gravity—2.149

OILED NUBUCK C99

modulus of rupture—1,174 psi

OILED NUBUCK C170

compressive strength—6,631 psi

OILED NUBUCK C241

abrasion resistance—5.38



PART NUMBERS

FULL VENEER:

1BSTKNS03011TN

THIN VENEER:

QB flat: 1BTVKNS03011QB

BX flat: 1BTVKNS03011BX

QB corner: 1BTVKNS03511QB

BX corner: 1BTVKNS03511BX

ARCHITECT/DESIGNER INFO

INSTALLATION SHOWN

Mortar: Western W-11

Joint Type: Raked

BIM DETAILS - SCAN

Revit, Hatch Patterns,

Seamless Textures,

3-Part Specs, DWGS,

SDS, Warranty



FULL VENEER

COMMON COVERAGE

Standard Joint
40 ft²/ton

Drystack
30 ft²/ton

Overgrout
50 ft²/ton

DIMENSIONS

l: 4" to 24" (14")

h: 4" to 12"

w: 3" to 5" (4")

Stone Ends shall be no less than 2-1/2" width

TYPICAL PIECE

Ends square; split top, bottom, and sides; bedface and splitface face and back; stone is squares and rectangles.

THIN VENEER

COMMON COVERAGE

Standard Joint
8 & 100 square feet

Drystack
6 & 75 ft²

Overgrout
10 & 110 ft²

DIMENSIONS

l: 4" to 24" (14")

h: 4" to 12"

w: 3/4" to 1-1/4" (1")

corner return 3" to 5"

TYPICAL PIECE

Ends square; split top, bottom, and sides; bedface and splitface face and sawn back; stone is squares and rectangles.



www.buechelstone.com