



CUT STONE
SILVERDALE
CUT STONE

GEOLOGY

limestone - quarried in USA

COLOR RANGE

yellows and creams to slight buffs with occasional veining and swirls.

CONSISTENCY BLOCK/SLAB

somewhat consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 134 =$
approx 134 pounds per cubic foot

ASTM TESTING DATA

SILVERDALE C97

water absorption—7.27%

density—134.1 pcf

specific gravity—2.149

SILVERDALE C99

modulus of rupture—1,174 psi

SILVERDALE C170

compressive strength—6,631 psi

SILVERDALE C241

abrasion resistance—5.38

PANEL INSTALLATION SHOWN

Mortar: Western W-100

Joint Type: struck

Size: h: 11 5/8", l: 23 5/8" - sanded finish



www.buechelstone.com

ARCHITECT/DESIGNER INFO

BIM DETAILS - SCAN
Revit, Hatch Patterns,
Seamless Textures,
3-Part Specs, DWGS,
SDS, Warranty



CUT STONE
SILVERDALE
CUT STONE

BRUSHED



BUSHHAMMERED



SANDBLASTED



VELOUR



SANDED

