



CUT STONE
SMOKED FOG
CUT STONE

GEOLOGY

limestone - quarried in USA

COLOR RANGE

gray, blue-gray, and charcoal; swirls common; occasional flecks of green

CONSISTENCY BLOCK/SLAB

somewhat consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 145 =$
approx 145 pounds per cubic foot

ASTM TESTING DATA

SMOKED FOG C97

water absorption—6.74%

density—137.2 pcf

specific gravity—2.2

SMOKED FOG C170

compressive strength

parallel dry - 6,471 psi

compressive strength

perpendicular dry—7,567 psi

compressive strength

parallel wet - 4175 psi

compressive strength

perpendicular wet—4,446 psi

PANEL INSTALLATION SHOWN

Mortar: Western Type - S

Joint Type: raked

Size: h: 1 1/8", l: 23 5/8" - sanded finish



www.buechelstone.com

ARCHITECT/DESIGNER INFO

BIM DETAILS - SCAN
Revit, Hatch Patterns,
Seamless Textures,
3-Part Specs, DWGS,
SDS, Warranty



CUT STONE
SMOKED FOG
CUT STONE

BRUSHED



BUSHHAMMERED



SANDBLASTED



VELOUR



SANDED

