



DIMENSIONAL

FOND DU LAC
TAILORED BLEND



GEOLOGY

dolomitic limestone - quarried in USA

COLOR RANGE

gray, light gray, buff, and white

CONSISTENCY PER PALLET

somewhat consistent

PALLET AMOUNTS

FULL VENEER (sold/ton) 4,000lbs each

THIN VENEER (sold/each) QB or BX

QUANTITY BOX - QB

1 - 100 sq ft of flats

1 - 50 lin ft of corners

SMALL BOX - BX

24 - 8 sq ft flat boxes, 192 total ft

20 - 8 lin ft corner boxes, 160 total feet

ASTM TESTING DATA

FOND DU LAC C97

water absorption—0.11%

FOND DU LAC C97

density—176.5 pcf

FOND DU LAC C99

modulus of rupture—2,480 psi

FOND DU LAC C170

compressive strength w/rift—31,810 psi

compressive strength across rift—26,550 psi

FOND DU LAC C880

flexural strength—1,740 psi

FULL VENEER

COMMON COVERAGE

Standard Joint 40 ft ² /ton	Drystack 30 ft ² /ton	Overgrout 50 ft ² /ton
---	-------------------------------------	--------------------------------------

DIMENSIONS

l: 6" to 42" (24")
h: 2-1/4"; h: 5";
h: 7-3/4"; h: 10-1/2"
w: 3" to 5" (4")

note: ± 1/8" on sawn heights - additional heights available

TYPICAL BLEND

20 percent 2-1/4"; 40 percent 5";
30 percent 7-3/4"; 10 percent 10-1/2"

TYPICAL PIECE

Ends square; sawn top and bottom;
sides are split; bedface face and back;
stone is rectangular in appearance with
length longer than height.

THIN VENEER

COMMON COVERAGE

Standard Joint 8 & 100 square feet	Drystack 6 & 75 ft ²	Overgrout 10 & 110 ft ²
---------------------------------------	------------------------------------	---------------------------------------

DIMENSIONS

l: 6" to 24" (12")
h: 2-1/4"; h: 5";
h: 7-3/4"; h: 10-1/2"
w: 3/4" to 1-1/4" (1")
corner return 3" to 5"

note: ± 1/8" on sawn heights - additional heights available

TYPICAL BLEND

20 percent 2-1/4"; 40 percent 5";
30 percent 7-3/4"; 10 percent 10-1/2"

TYPICAL PIECE

Ends square; sawn top and bottom; sides
are split; bedface face and sawn back;
stone is rectangular in appearance with
length longer than height.

PART NUMBERS

FULL VENEER:

1BSTBUE02009TN

THIN VENEER:

QB flat: 1BTVBUE02006QB

BX flat: 1BTVBUE02006BX

QB corner: 1BTVBUE02506QB

BX corner: 1BTVBUE02506BX

ARCHITECT/DESIGNER INFO

INSTALLATION SHOWN

Mortar: Laticrete - Std. Gray

Joint Type: Raked

BIM DETAILS - SCAN

Revit, Hatch Patterns,
Seamless Textures,
3-Part Specs, DWGS,
SDS, Warranty



www.buechelstone.com