



OUTCROPPINGS  
*FOND DU LAC  
 WEATHEREDGE  
 OUTCROPPINGS*



**GEOLOGY**

dolomitic limestone

**BASIC USE**

for retaining ground or  
 as an accent in landscaping

**COLOR RANGE**

gray, light gray to white, buff;  
 face is brown, buff, tan, and gold

**CONSISTENCY PER PALLET**

somewhat consistent

**WEIGHT CALCULATED IN INCHES**

$l \times w \times h / 1728$  (inches cubed)  $\times 170$   
 = approx 170 pounds per cubic foot

**PALLET**

4,000 pounds or as product fits

standard size: 3 to 5 pieces per pallet;  
 2 to 3 man: 10 to 12 pieces per pallet  
 1 to 2 man: 16 to 18 pieces per pallet;

**COVERAGES**

coverages calculated as specified per  
 project

**PART NUMBERS**

FOND DU LAC WEATHEREDGE  
 OUTCROPPINGS  
 1OUTBUE02002TN  
 2 to 3 man  
 1OUTBUE02010TN  
 1 to 2 man  
 1OUTBUE02017TN

**ASTM TESTING DATA**

FOND DU LAC C97  
 water absorption—0.36%  
 density—174.2 pcf  
 FOND DU LAC C99  
 modulus of rupture—1,470 psi  
 FOND DU LAC C170  
 compressive strength  
 w/rift—29,040 psi  
 compressive strength  
 across rift—34,240 psi  
 FOND DU LAC C880  
 flexural strength—1,740 psi

FOND DU LAC WEATHEREDGE  
 OUTCROPPINGS

**DIMENSIONS**

l: 18" to 60"  
 h: 5" to 12"  
 w: 18" to 60"  
 note: lengths and widths are irregular  
 shapes 18 inches to 60 inches in  
 diameter

2 to 3 MAN OUTCROPPINGS

**DIMENSIONS**

l: 24" to 36"  
 h: 4" to 8"  
 w: 24" to 36"  
 note: lengths and widths are irregular  
 shapes 24 inches to 36 inches in  
 diameter

1 to 2 MAN OUTCROPPINGS

**DIMENSIONS**

l: 12" to 30"  
 h: 4" to 8"  
 w: 12" to 30"  
 note: lengths and widths are irregular  
 shapes 12 inches to 30 inches in  
 diameter

**TYPICAL PIECE**

ends irregular; natural cleft top and  
 bottom; natural split sides with at  
 least one face being seamface or  
 weatheredge; stone is random shapes

