

# OUTCROPPING STEPS

*CHILTON WEATHEREDGE  
OUTCROPPING STEPS*



## GEOLOGY

dolomitic limestone

## BASIC USE

for steps

## COLOR RANGE

top or bottom is purple, lavender, mauve, gray, buff, blue, and brown; face is brown, buff, orange, yellow, red, & rust

## CONSISTENCY PER PALLET

somewhat consistent

## WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$  (inches cubed)  $\times 170$   
= approx 170 pounds per cubic foot

## PALLET

4,000 pounds or as product fits

## COVERAGES

calculated as specified per project

## DIMENSIONS

l: 18" to 60"

h: 5" to 8"

w: 18" to 60"

note: lengths and widths are irregular shapes

18 inches to 60 inches in diameter

## TYPICAL PIECE

ends irregular; natural cleft top and bottom; natural split sides with at least one face being seamface or weatheredge; stone is somewhat square but may be irregular



## ASTM TESTING DATA

CHILTON C97

water absorption—0.08%

density—177.4 pcf

CHILTON C99

modulus of rupture—1,220 psi

CHILTON C170

compressive strength

w/rift—50,560 psi

compressive strength

across rift—38,090 psi

CHILTON C880

flexural strength—3,070 psi

## PART NUMBERS

1OUTBUE01004TN

