OUTCROPPING STEPS

FOND DU LAC
WEATHEREDGE
OUTCROPPING STEPS

GEOLOGY
dolomitic limestone

BASIC USE
for steps

COLOR RANGE
gray, light gray to white, buff;
face is brown, buff, tan, and gold

CONSISTENCY PER PALLET
somewhat consistent

WEIGHT CALCULATED IN INCHES
l x w x h / 1728 (inches cubed) x 170
= approx 170 pounds per cubic foot

PALLET
4,000 pounds or as product fits

COVERAGES
calculated as specified per project

DIMENSIONS
l: 18” to 60”
h: 5” to 8”
w: 18” to 60”
note: lengths and widths are irregular shapes
18 inches to 60 inches in diameter

TYPICAL PIECE
ends irregular; natural cleft top and bottom; natural split sides with at least one face being seamface or weatheredge; stone is somewhat square but may be irregular

ASTM TESTING DATA

FOND DU LAC C97
water absorption—0.36%
density—174.2 pcf
FOND DU LAC C99
modulus of rupture—1,470 psi
FOND DU LAC C170
compressive strength w/rift—29,040 psi
compressive strength across rift—34,240 psi
FOND DU LAC C880
flexural strength—1,740 psi

PART NUMBERS
1OUTBUE02004TN