



# OUTCROPPINGS

CHILTON WEATHEREDGE  
OUTCROPPINGS



## GEOLOGY

dolomitic limestone

## BASIC USE

for retaining ground or as an accent in landscaping

## COLOR RANGE

top or bottom is purple, lavender, mauve, gray, buff, blue, and brown; face is brown, buff, orange, yellow, red, and rust

## CONSISTENCY PER PALLET

somewhat consistent

## WEIGHT CALCULATED IN INCHES

l x w x h / 1728 (inches cubed) x 170  
= approx 170 pounds per cubic foot

## PALLET

4,000 pounds or as product fits

standard size: 3 to 5 pieces per pallet

2 to 3 man: 10 to 12 pieces per pallet

1 to 2 man: 16 to 18 pieces per pallet

## COVERAGES

coverages calculated as specified per project

## CHILTON WEATHEREDGE

### OUTCROPPINGS

#### DIMENSIONS

l: 18" to 60"

h: 5" to 12"

w: 18" to 60"

note: lengths and widths are irregular shapes

18 inches to 60 inches in diameter

#### 2 to 3 MAN OUTCROPPINGS

##### DIMENSIONS

l: 24" to 36"

h: 4" to 8"

w: 24" to 36"

note: lengths and widths are irregular shapes 24 inches to 36 inches in diameter

#### 1 to 2 MAN OUTCROPPINGS

##### DIMENSIONS

l: 12" to 30"

h: 4" to 8"

w: 12" to 30"

note: lengths and widths are irregular shapes 12 inches to 30 inches in diameter

#### TYPICAL PIECE

ends irregular; natural cleft top and bottom; natural split sides with at least one face being seamface or weatheredge; stone is random shapes

## PART NUMBERS

CHILTON WEATHEREDGE

OUTCROPPINGS

1OUTBUE01002TN

2 to 3 man

1OUTBUE01010TN

1 to 2 man

1OUTBUE01016TN

## ASTM TESTING DATA

CHILTON C97

water absorption—0.08%

density—177.4 pcf

CHILTON C99

modulus of rupture—1,220 psi

CHILTON C170

compressive strength

w/rift—50,560 psi

compressive strength

across rift—38,090 psi

CHILTON C880

flexural strength—3,070 psi

