



OUTCROPPINGS

FOND DU LAC
OUTCROPPINGS



GEOLOGY

dolomitic limestone

BASIC USE

for retaining ground or
as an accent in landscaping

COLOR RANGE

gray, light gray to white, buff

CONSISTENCY PER PALLET

consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

PALLET

4,000 pounds or as product fits

COVERAGES

coverages calculated as specified per
project

FOND DU LAC OUTCROPPINGS

DIMENSIONS

l: 18" to 60"

h: 5" to 12"

w: 18" to 60"

note: lengths and widths are irregular
shapes 18 inches to 60 inches in
diameter

2 to 3 MAN OUTCROPPINGS

DIMENSIONS

l: 24" to 36"

h: 4" to 8"

w: 24" to 36"

note: lengths and widths are irregular
shapes 24 inches to 36 inches in
diameter

1 to 2 MAN OUTCROPPINGS

DIMENSIONS

l: 12" to 30"

h: 4" to 8"

w: 12" to 30"

note: lengths and widths are irregular
shapes 12 inches to 30 inches in
diameter

TYPICAL PIECE

ends irregular; natural cleft top and
bottom; natural split sides; stone is
random shapes

PART NUMBERS

FOND DU LAC OUTCROPPINGS

1OUTBUE02001TN

2 to 3 man

1OUTBUE02009TN

1 to 2 man

1OUTBUE02015TN

ASTM TESTING DATA

FOND DU LAC C97

water absorption—0.36%

density—174.2 pcf

FOND DU LAC C99

modulus of rupture—1,470 psi

FOND DU LAC C170

compressive strength

w/rift—29,040 psi

compressive strength

across rift—34,240 psi

FOND DU LAC C880

flexural strength—1,740 psi

