



**PATIO &
PAVING**
*BLUESTONE
FLAGSTONE*

GEOLOGY: sandstone

BASIC USE

on patios and walkways; stone is dryset
in gravel bed or mortared in

COLOR RANGE

green, blue, and brown

CONSISTENCY PER PALLET

consistent

**WEIGHT CALCULATED IN
INCHES**

l x w x h / 1728 (inches cubed) x 165
= approx 165 pounds per cubic foot

PALLET

4,000 pounds stand-up or as product fits

COVERAGES

3/4" to 1-1/2" 130 square feet/ton

1-1/2" to 2-1/2" square feet/ton

DIMENSIONS

l: 18" to 48"

h: 3/4" to 1-1/2" or

h: 1-1/2" to 2-1/2"

w: 18" to 48"

note: lengths and widths are irregular
shapes 18 inches to 48 inches in
diameter

TYPICAL PIECE

ends irregular; natural cleft top and
bottom; natural split sides; stone is
random shapes

PART NUMBERS

1-1/2" to 2-1/2": 1PATNEW01002TN

3/4" to 1-1/2": 1PATNEW01001TN

ASTM TESTING DATA

BLUESTONE C97

water absorption—1.57%

BLUESTONE C170

compressive strength

w/rift—10,200 psi

compressive strength

across rift—17,400 psi

BLUESTONE C880

flexural strength w/rift—1,600 psi

flexural strength across rift—2,120 psi

BLUESTONE C241

abrasion resistance—28

