



**PATIO &  
PAVING**  
*BLUESTONE  
PATTERNED FLAGSTONE  
THERMALLED*

**GEOLOGY**

quartzitic sandstone

**BASIC USE**

on patios and walkways; stone is dryset in gravel bed or mortared in

**COLOR RANGE**

green, blue, and brown; somewhat variegated unless specified per project

**CONSISTENCY PER PALLET**

somewhat consistent

**WEIGHT CALCULATED IN INCHES**

l x w x h / 1728 (inches cubed) x 165  
= approx 165 pounds per cubic foot

**PALLET**

100 square feet - Pattern A

Specific sizes available upon request

**DIMENSIONS**

l: 12"; 24"

h: 1 1/2"

w: 12"; 24"; 36"

note: ± 1/8" on sawn heights and widths

**PATTERN A SIZES PER PALLET**

13 pieces - 12" x 12"; 10 pieces - 12" x 24";  
1 piece - 12" x 36"; 10 pieces - 24" x 24";  
and 4 pieces - 24" x 36"

note: all pieces cut to 1/2" size

**TYPICAL PIECE**

ends square; sawn and thermalled top;  
sawn sides, face, and back; natural cleft  
bottom; stone is squares and rectangles

**PART NUMBERS**

Pattern A: 1PATNEW01001EA

BLUE BLUE Pattern A: 1PATNEW01008EA

**ASTM TESTING DATA**

**BLUESTONE C97**

water absorption—1.57%

**BLUESTONE C170**

compressive strength

w/rift—10,200 psi

compressive strength

across rift—17,400 psi

**BLUESTONE C880**

flexural strength w/rift—1,600 psi

flexural strength across rift—2,120 psi

**BLUESTONE C241**

abrasion resistance—28

