

PATIO &
PAVING
CHILTON
COLONIAL
PAVERS



GEOLOGY

dolomitic limestone

BASIC USE

on patios and walkways; stone is dryset
in gravel bed or mortared in

COLOR RANGE

purple, lavender, mauve, gray, buff, blue,
and brown; white from tumbling

CONSISTENCY PER PALLET

somewhat consistent

**WEIGHT CALCULATED IN
INCHES**

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

PALLET

4,000 pounds or as product fits

COVERAGES

Dependent on type of install

DIMENSIONS

l: 5" or 10"

h: 5"

w: 1", 2", 3", 4", 5"

+/- 1" on height

+/- 1" on length

note: $\pm 1/8$ " on sawn heights

TYPICAL PIECE

ends square; sawn two sides; sides
are split; bedface top and/or bottom;
bottom may be sawn; stone rounded
from tumbling



ASTM TESTING DATA

CHILTON C97

water absorption—0.08%

density—177.4 pcf

CHILTON C99

modulus of rupture—1,220 psi

CHILTON C170

compressive strength

w/rift—50,560 psi

compressive strength

across rift—38,090 psi

CHILTON C880

flexural strength—3,070 psi

PART NUMBERS

5" x 5" x 1": 1PAVBUE01001TN

5" x 5" x 2": 1PAVBUE01003TN

5" x 5" x 3": 1PAVBUE01005TN

5" x 5" x 4": 1PAVBUE01007TN

5" x 5" x 5": 1PAVBUE01009TN

5" x 10" x 1": 1PAVBUE01002TN

5" x 10" x 2": 1PAVBUE01004TN

5" x 10" x 3": 1PAVBUE01006TN

5" x 10" x 4": 1PAVBUE01008T

5" x 10" x 5": 1PAVBUE01010TN

