



STEPS

CHILTON SNAPPED STEPS



PART NUMBERS
18"x36": 1STEBUE01001EA
24"x36": 1STEBUE01006EA
18"x48": 1STEBUE01002EA
24"x48": 1STEBUE01004EA

ASTM TESTING DATA

CHILTON C97
water absorption—0.08%
density—177.4 pcf
CHILTON C99
modulus of rupture—1,220 psi
CHILTON C170
compressive strength
w/rift—50,560 psi
compressive strength
across rift—38,090 psi
CHILTON C880
flexural strength—3,070 psi

GEOLOGY

dolomitic limestone

BASIC USE

for steps

COLOR RANGE

top or bottom is purple, lavender, mauve, gray, buff, blue, and brown; face is gray to charcoal with occasional mauves

COLOR CONSISTENCY PER PALLET

somewhat consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) $\times 170$
= approx 170 pounds per cubic foot

STEPS PER PALLET

18" x 36" = 8 steps per pallet
24" x 36" = 5 steps per pallet
18" x 48" = 6 steps per pallet
24" x 48" = 5 steps per pallet

COVERAGES

calculated as specified per project

18"x36" SNAPPED STEPS

DIMENSIONS

l: 35" to 37"
h: 5" to 8"
w: 17" to 19"

24"x36" SNAPPED STEPS

DIMENSIONS

l: 35" to 37"
h: 5" to 8"
w: 23" to 25"

18"x48" SNAPPED STEPS

DIMENSIONS

l: 47" to 49"
h: 5" to 8"
w: 17" to 19"

24"x48" SNAPPED STEPS

DIMENSIONS

l: 47" to 49"
h: 5" to 8"
w: 23" to 25"

TYPICAL PIECE

ends square; natural cleft top and bottom; split sides, face and back; stone is rectangular; custom sizing by request