



# STEPS

FOND DULAC  
WEATHEREDGE STEPS



## GEOLOGY

dolomitic limestone

## BASIC USE

for steps

## COLOR RANGE

gray, light gray to white, buff;  
face is brown, buff, tan, and gold

## CONSISTENCY PER PALLET

somewhat consistent

## WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$  (inches cubed)  $\times 170$   
= approx 170 pounds per cubic foot

## STEPS PER PALLET

18" x 36" = 8 steps per pallet

24" x 36" = 5 steps per pallet

18" x 48" = 6 steps per pallet

24" x 48" = 5 steps per pallet

## COVERAGES

coverages calculated as specified per project

## PART NUMBERS

18" x 36": 1STEBUE02003EA

24" x 36": 1STEBUE02013EA

18" x 48": 1STEBUE02009EA

24" x 48": 1STEBUE02012EA

## ASTM TESTING DATA

FOND DU LAC C97

water absorption—0.36%

density—174.2 pcf

FOND DU LAC C99

modulus of rupture—1,470 psi

FOND DU LAC C170

compressive strength

w/rift—29,040 psi

compressive strength

across rift—34,240 psi

FOND DU LAC C880

flexural strength—1,740 psi

## 18" x 36" WEATHEREDGE STEPS

DIMENSIONS

l: 35" to 37"

h: 5" to 8"

w: 17" to 19"

## 24" x 36" WEATHEREDGE STEPS

DIMENSIONS

l: 35" to 37"

h: 5" to 8"

w: 23" to 25"

## 18" x 48" WEATHEREDGE STEPS

DIMENSIONS

l: 47" to 49"

h: 5" to 8"

w: 17" to 19"

## 24" x 48" WEATHEREDGE STEPS

DIMENSIONS

l: 47" to 49"

h: 5" to 8"

w: 23" to 25"

## TYPICAL PIECE

ends square; natural cleft top and bottom; split or natural sides; split back; face is seamface or weatheredge; stone is rectangular; custom sizing by request

