

STEPS

MILL CREEK SNAPPED STEPS



GEOLOGY

dolomitic limestone

BASIC USE

for steps

COLOR RANGE

top or bottom buff to brown;
face and sides light gray to buff
with occasional blue veins

COLOR CONSISTENCY PER PALLET

consistent

WEIGHT CALCULATED IN INCHES

$l \times w \times h / 1728$ (inches cubed) x 170
= approx 170 pounds per cubic foot

STEPS PER PALLET

18" x 36" = 8 steps per pallet

24" x 36" = 5 steps per pallet

18" x 48" = 6 steps per pallet

24" x 48" = 5 steps per pallet



COVERAGES

calculated as specified per project

18"x36" SNAPPED STEPS

DIMENSIONS

l: 35" to 37"

h: 5" to 8"

w: 17" to 19"

24"x36" SNAPPED STEPS

DIMENSIONS

l: 35" to 37"

h: 5" to 8"

w: 23" to 25"

18"x48" SNAPPED STEPS

DIMENSIONS

l: 47" to 49"

h: 5" to 8"

w: 17" to 19"

24"x48" SNAPPED STEPS

DIMENSIONS

l: 47" to 49"

h: 5" to 8"

w: 23" to 25"

TYPICAL PIECE

ends square; natural cleft top and
bottom; split sides, face and back; stone
is rectangular; custom sizing by request

ASTM TESTING DATA

MILL CREEK C97

water absorption—0.66%

density—173.0 pcf

MILL CREEK C99

modulus of rupture—2,072 psi

MILL CREEK C170

compressive strength—26,260 psi

MILL CREEK C880

flexural strength—1,374 psi

PART NUMBERS

18"x36": 1STELEN01002EA

24"x36": 1STELEN01004EA

18"x48": 1STELEN01001EA

24"x48": 1STELEN01006EA

