



PATIO & PAVING

FOND DU LAC
SAWN PAVING

GEOLOGY

dolomitic limestone

BASIC USE

on patios and walkways; stone is dryset in gravel bed or mortared in

COLOR RANGE

gray, light gray, buff, and white

CONSISTENCY PER PALLET

somewhat consistent

WEIGHT CALCULATED IN INCHES

l x w x h / 1728 (inches cubed) x 170
= approx 170 pounds per cubic foot

PALLET

4,000 pounds

COVERAGES

1" to 2" 80 square feet / ton

1-3/4" to 2-1/2" 65 ft²/ton

DIMENSIONS

l: 4" to 24"

h: 1" to 2" or

h: 1-3/4" to 2-1/2"

w: 4" to 24"

note: ± 1/8" on sawn heights

note: lengths and widths are irregular
shapes 4" to 24" in diameter

TYPICAL PIECE

natural cleft at the top and bottom; sawn ends; sawn to heights of 4" with random lengths

PART NUMBERS

1" to 2": 1-PA-1049-PA

1-3/4" to 2-1/2": 1-PA-1044-PA

ASTM TESTING DATA

FOND DU LAC C97

water absorption—0.36%

density—174.2 pcf

FOND DU LAC C99

modulus of rupture—1,470 psi

FOND DU LAC C170

compressive strength

w/rift—29,040 psi

compressive strength

across rift—34,240 psi

FOND DU LAC C880

flexural strength—1,740 psi

