



LEDGESTONE

CINNAMON BARK
LEDGESTONE



GEOLOGY

gneiss - quarried in Bulgaria, packaged in USA

COLOR RANGE

silver, gold, and brown

CONSISTENCY PER PALLET

somewhat consistent

PALLET AMOUNTS

FULL VENEER (sold/ton) 4,000lbs each

THIN VENEER (sold/each) QB or BX

QUANTITY BOX - QB

1 - 100 sq ft of flats

1 - 50 lin ft of corners

SMALL BOX - BX

24 - 8 sq ft flat boxes, 192 total ft

20 - 8 lin ft corner boxes, 160 total feet

ASTM TESTING DATA

CINNAMON BARK C97

water absorption—0.29%

density—177.8 pcf

CINNAMON BARK C170

compressive strength—15,530 psi

CINNAMON BARK LEDGESTONE VENEER GENERAL INSTALL NOTES

install 30% bedface out to achieve desired square footage for a typical blend

THIN VENEER INSTALL NOTES

only use 25% corners with flats toothed in to the remaining balance to accomplish color range consistency on the corners

PART NUMBERS

FULL VENEER:

N/A

THIN VENEER:

QB flat: 1BTVBUE06001QB

BX flat: 1BTVBUE06001BX

QB corner: 1BTVBUE06501QB

BX corner: 1BTVBUE06501BX

ARCHITECT/DESIGNER INFO

INSTALLATION SHOWN

Mortar: Laticrete MVIS

Joint Type: Drystack

BIM DETAILS - SCAN

Revit, Hatch Patterns,
Seamless Textures,
3-Part Specs, DWGS,
SDS, Warranty



FULL VENEER

COMMON COVERAGE

Standard Joint 35 ft ² /ton	Drystack 25 ft ² /ton	Overgrout 45 ft ² /ton
---	-------------------------------------	--------------------------------------

DIMENSIONS

N/A - Thin Veneer Only

THIN VENEER

COMMON COVERAGE

Standard Joint 8 & 100 square feet	Drystack 6 & 75 ft ²	Overgrout 10 & 110 ft ²
---------------------------------------	------------------------------------	---------------------------------------

DIMENSIONS

l: 4" to 16" (8")

h: 3/4" to 2-1/4"

w: 3/4" to 1-1/4" (1")

corner return 3" to 5"

TYPICAL BLEND

up to 30 percent may be sawn top and bottom with a bedface face; face of stone cannot have a sawn finish

TYPICAL PIECE

Ends random; natural cleft or sawn top and bottom; face and sides natural split or seamface; back sawn; stone is linear.



www.buechelstone.com