

# LEDGESTONE

WHISPERING PINES  
LEDGESTONE



## GEOLOGY

quartzitic sandstone - quarried in USA

## COLOR RANGE

75% Whispering Pines Ledgestone  
25% Whispering Pines Fieldstone

## CONSISTENCY PER PALLET

somewhat consistent

## PALLET AMOUNTS

FULL VENEER (sold/ton) 4,000lbs each

THIN VENEER (sold/each) QB or BX

QUANTITY BOX - QB

1 - 100 sq ft of flats

1 - 50 lin ft of corners

SMALL BOX - BX

24 - 8 sq ft flat boxes, 192 total ft

20 - 8 lin ft corner boxes, 160 total feet

## ASTM TESTING DATA

WHISPERING PINES C97

water absorption—0.96%

WHISPERING PINES C97

specific gravity—2.65

WHISPERING PINES C99

modulus of rupture—4,550 psi

WHISPERING PINES C170

compressive strength—11,630 psi

WHISPERING PINES C880

flexural strength—2,120 psi wet—

12,920 psi | 11,220 psi

compressive strength perpendicular

dry—n/a | 15,300 psi

## PART NUMBERS

FULL VENEER:

1BSTCAT01001TN

THIN VENEER:

QB flat: 1BTVCAT01001QB

BX flat: 1BTVCAT01001BX

QB corner: 1BTVCAT01501QB

BX corner: 1BTVCAT01501BX

## ARCHITECT/DESIGNER INFO

INSTALLATION SHOWN

Mortar: Laticrete MVIS

Joint Type: Drystack

BIM DETAILS - SCAN

Revit, Hatch Patterns,

Seamless Textures,

3-Part Specs, DWGS,

SDS, Warranty



## FULL VENEER

COMMON COVERAGE

Standard Joint  
35 ft<sup>2</sup>/ton

Drystack  
25 ft<sup>2</sup>/ton

Overgrout  
45 ft<sup>2</sup>/ton

DIMENSIONS

l: 6" to 18" (12")

h: 1" to 4"

w: 3" to 5" (4")

TYPICAL PIECE

Ends random; natural cleft top and bottom; back, face, and sides natural split, back split or sawn; stone is linear.

## THIN VENEER

COMMON COVERAGE

Standard Joint  
8 & 100 square feet

Drystack  
6 & 75 ft<sup>2</sup>

Overgrout  
10 & 110 ft<sup>2</sup>

DIMENSIONS

l: 6" to 18" (10")

h: 1" to 4"

w: 3/4" to 1-1/4" (1")  
corner return 3" to 5"

TYPICAL PIECE

Ends random; natural cleft top and bottom; back, face, and sides natural split, back sawn; stone is linear.



www.buechelstone.com