

MOSAIC
JUTE CLOTH
WEBWALL



GEOLOGY

limestone - quarried in USA

COLOR RANGE

tans, browns, light grays, and whites

CONSISTENCY PER PALLET

somewhat consistent

PALLET AMOUNTS

FULL VENEER (sold/ton) 4,000lbs each

THIN VENEER (sold/each) QB or BX

QUANTITY BOX - QB

1 - 100 sq ft of flats

1 - 50 lin ft of corners

SMALL BOX - BX

24 - 8 sq ft flat boxes, 192 total ft

20 - 8 lin ft corner boxes, 160 total feet

ASTM TESTING DATA

JUTE CLOTH C97

water absorption—10.03%

specific gravity — 1.995 to 2.008

density—125.1 lbs/ft³

JUTE CLOTH C170

dry perpendicular—4,040 psi

wet perpendicular—1,830 psi

dry parallel—3,210 psi

wet parallel—1,480 psi

JUTE CLOTH C880

flexural strength -wet —440 psi

flexural strength -dry —600 psi



PART NUMBERS

FULL VENEER:

1BSTKNS01008TN

THIN VENEER:

QB flat: 1BTVKNS01008QB

BX flat: 1BTVKNS010086BX

QB corner: 1BTVKNS01508QB

BX corner: 1BTVKNS01508BX

FULL VENEER

COMMON COVERAGE

Standard Joint
40 ft²/ton

Drystack
30 ft²/ton

Overgrout
50 ft²/ton

DIMENSIONS

l: 3" to 16" dia.

h: 3" to 16" dia.

w: 3" to 5" (4")

note: lengths and heights are irregular
shapes 3 inches to 16 inches in diameter

TYPICAL PIECE

Ends irregular; natural split sides;
bedface face and back; stone is random
shapes.

THIN VENEER

COMMON COVERAGE

Standard Joint
8 & 100 square feet

Drystack
6 & 75 ft²

Overgrout
10 & 110 ft²

DIMENSIONS

l: 3" to 16" dia.

h: 3" to 16" dia.

w: 3/4" to 1-1/4" (1")

corner return 3" to 6"

note: lengths and heights are irregular
shapes 3 inches to 12 inches in diameter

TYPICAL PIECE

Ends irregular; natural split sides;
bedface face and sawn back; stone is
random shapes.

ARCHITECT/DESIGNER INFO

INSTALLATION SHOWN

Mortar: Quikrete Type S

Joint Type: Raked

BIM DETAILS - SCAN

Revit, Hatch Patterns,
Seamless Textures,
3-Part Specs, DWGS,
SDS, Warranty



www.buechelstone.com