

MOSAIC  
OILED NUBUCK  
FIELDSTONE



**GEOLOGY**

limestone - quarried in USA

**COLOR RANGE**

buff, brown, tans, gray, and black

**CONSISTENCY PER PALLET**

somewhat consistent

**PALLET AMOUNTS**

FULL VENEER (sold/ton) 4,000lbs each

THIN VENEER (sold/each) QB or BX

QUANTITY BOX - QB

1 - 100 sq ft of flats

1 - 50 lin ft of corners

SMALL BOX - BX

24 - 8 sq ft flat boxes, 192 total ft

20 - 8 lin ft corner boxes, 160 total feet

**ASTM TESTING DATA**

OILED NUBUCK C97

water absorption—7.27%

OILED NUBUCK C97

density—134.1 pcf

OILED NUBUCK C97

specific gravity—2.149

OILED NUBUCK C99

modulus of rupture—1,174 psi

OILED NUBUCK C170

compressive strength—6,631 psi

OILED NUBUCK C241

abrasion resistance—5.38



**PART NUMBERS**

FULL VENEER:

1BSTKNS01009TN

THIN VENEER:

QB flat: 1BTBKNS01009QB

BX flat: 1BTVKNS01009BX

QB corner: 1BTVKNS01509QB

BX corner: 1BTVKNS01509BX

**ARCHITECT/DESIGNER INFO**

INSTALLATION SHOWN

Mortar: Quikrete Type S

Joint Type: Raked

BIM DETAILS - SCAN

Revit, Hatch Patterns,

Seamless Textures,

3-Part Specs, DWGS,

SDS, Warranty



**FULL VENEER**

**COMMON COVERAGE**

Standard Joint  
40 ft<sup>2</sup>/ton

Drystack  
30 ft<sup>2</sup>/ton

Overgrout  
50 ft<sup>2</sup>/ton

**DIMENSIONS**

l: 3" to 16" dia.

h: 3" to 16" dia.

w: 3" to 5" (4")

note: lengths and heights are irregular  
shapes 3 inches to 16 inches in diameter

**TYPICAL PIECE**

Ends irregular; natural split and rounded  
sides; bedface face and back; stone is  
random shapes.

**THIN VENEER**

**COMMON COVERAGE**

Standard Joint  
8 & 100 square feet

Drystack  
6 & 75 ft<sup>2</sup>

Overgrout  
10 & 110 ft<sup>2</sup>

**DIMENSIONS**

l: 3" to 16" dia.

h: 3" to 16" dia.

w: 3/4" to 1-1/4" (1")

corner return 3" to 6"

note: lengths and heights are irregular  
shapes 3 inches to 12 inches in diameter

**TYPICAL PIECE**

Ends irregular; natural split and rounded  
sides; bedface face and sawn back;  
stone is random shapes.



www.buechelstone.com