TAILORED FIELDLEDGE

BARNWOOD BLUE
TAILORED FIELDLEDGE

GEOLOGY
schist - quarried in USA

COLOR RANGE
grays, dark grays, charcoals, whites, blues, tans with occasional greens, buffs, and blacks

CONSISTENCY PER PALLET
somewhat consistent

PALLET AMOUNTS
FULL VENEER (sold/ton) 4,000lbs each
THIN VENEER (sold/each) QB or BX
QUANTITY BOX - QB
1 - 100 sq ft of flats
1 - 50 lin ft of corners
SMALL BOX - BX
24 - 8 sq ft flat boxes, 192 total ft
20 - 8 lin ft corner boxes, 160 total feet

ASTM TESTING DATA
BARNWOOD BLUE C97
water absorption—0.5%
specific gravity—2.75
density—171.8 pcf
BARNWOOD BLUE C99
modulus of rupture perpendicular dry—3,490 psi
modulus of rupture perpendicular wet—2,920 psi
BARNWOOD BLUE C170
compressive strength parallel dry—12,260 psi
compressive strength parallel wet—9,770 psi
compressive strength perpendicular dry—15,300 psi
compressive strength perpendicular wet—11,220 psi dry—n/a | 15,300 psi

THIN VENEER

COMMON COVERAGE
Figured for Drystacked Joint Only
8 & 100 square feet

DIMENSIONS
l: 3" to 24" (8")
h: 2"; h: 4"; h: 6"
w: 3/4" to 1-1/4" (1")
corner return N/A - Butt Jointed
note: sawn heights with varying lengths having rough irregular ends

TYPICAL PIECE
Ends irregular; random lengths; sawn top and bottom; sides not square; bedface and split face and sawn back; overall appearance of stone will be linear when installed.

SEE CORNER EXAMPLE TO THE RIGHT

CORNER INSTALLATION

PART NUMBERS
FULL VENEER:
N/A
THIN VENEER:
QB flat: 1-TF-1015-QB
BX flat: 1-TF-1015-BX
QB corner: 1-TC-1015-QB
BX corner: 1-TC-1015-BX

ARCHITECT/DESIGNER INFO
INSTALLATION SHOWN
Mortar: Laticrete MVIS
Joint Type: Drystack

BIM DETAILS - SCAN
Revit, Hatch Patterns, Seamless Textures, 3-Part Specs, DWGS, SDS, Warranty